

# SAFETY DATA SHEET

Version 8.13 Revision Date 09/08/2024 Print Date 09/09/2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifiers

Product name : Acetone EMPLURA®

 Product Number
 : 8.22251

 Catalogue No.
 : 822251

 Brand
 : Millipore

 Index-No.
 : 606-001-00-8

 CAS-No.
 : 67-64-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Solvent, Chemical for synthesis

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The

product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Millipore - 8.22251

Page 1 of 13



For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal Word Danger

Hazard Statements

H225 Highly flammable liquid and vapor.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

**Precautionary Statements** 

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/ shower.

for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal

plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Formula : C3H6O

Molecular weight : 58.08 g/mol

CAS-No. : 67-64-1

EC-No. : 200-662-2

Index-No. : 606-001-00-8

Millipore - 8.22251

MILLIPORE

Page 2 of 13

Component	Classification	Concentration
acetone		
	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336 Concentration limits: >= 20 %: STOT SE 3, H336;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first-aid measures

#### **General advice**

Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Call in physician.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment needed No data available

### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

# Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Millipore - 8.22251



# 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

### **5.3** Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

#### 5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

#### 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

# 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb $\mathbb{R}$ ). Dispose of properly. Clean up affected area.

#### 6.4 Reference to other sections

For disposal see section 13.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

### Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

### Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

## **Hygiene measures**

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

### Storage conditions

Millipore - 8.22251

Page 4 of 13

Protected from light.Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

### Storage class

Storage class (TRGS 510): 3: Flammable liquids

# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

### **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

**Ingredients with workplace control parameters** 

Ingredients with				
Component	CAS-No.	Value	Control	Basis
			parameters	
acetone	67-64-1	TWA	250 ppm	USA. ACGIH Threshold Limit
				Values (TLV)
	Remarks	Not classifiable as a human carcinogen		
		STEL	500 ppm	USA. ACGIH Threshold Limit
				Values (TLV)
		Not classifiable as a human carcinogen		
		TWA	250 ppm	USA. NIOSH Recommended
			590 mg/m3	Exposure Limits
		TWA	1,000 ppm	USA. Occupational Exposure
			2,400 mg/m3	Limits (OSHA) - Table Z-1
				Limits for Air Contaminants
		С	3,000 ppm	California permissible exposure
				limits for chemical
				contaminants (Title 8, Article
				107)
		PEL	500 ppm	California permissible exposure
			1,200 mg/m3	limits for chemical
				contaminants (Title 8, Article
				107)
		STEL	750 ppm	California permissible exposure
			1,780 mg/m3	limits for chemical
				contaminants (Title 8, Article
				107)

**Biological occupational exposure limits** 

biological occupational exposure inities					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis
acetone	67-64-1	Acetone	25 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (	(As soon as	s possible after exp	posure ceases)

Millipore - 8.22251 Page 5 of 13



### 8.2 Exposure controls

### **Appropriate engineering controls**

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

### Personal protective equipment

### **Eye/face protection**

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 480 min

Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Latex gloves

Minimum layer thickness: 0.6 mm Break through time: 10 min

Material tested:Lapren® (KCL 706 / Aldrich Z677558, Size M)

#### **Body Protection**

Flame retardant antistatic protective clothing.

### **Respiratory protection**

Recommended Filter type: Filter type AX

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented. required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

# **Control of environmental exposure**

Do not let product enter drains. Risk of explosion.



### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor pungent, weakly aromatic

c) Odor Threshold 0.1 ppm

d) pH 5 - 6 at 395 g/l at 20 °C (68 °F)

e) Melting point/ range: -94.0 °C (-137.2 °F)

point/freezing point

f) Initial boiling point 56.0 °C 132.8 °F at 1,013 hPa and boiling range

g) Flash point -17.0 °C (1.4 °F) - closed cup

h) Evaporation rate No data availablei) Flammability (solid, No data available

gas)

k) Vapor pressure 245.3 hPa at 20.0 °C (68.0 °F)

I) Vapor density No data available

m) Density 0.79 g/cm3 at 20 °C (68 °F)

Relative density No data available

n) Water solubility soluble, in all proportions

o) Partition coefficient: No data available

n-octanol/water

p) Autoignition 465.0 °C (869.0 °F) temperature

q) Decomposition Distillable in an undecomposed state at normal pressure. temperature

r) Viscosity No data availables) Explosive properties No data available

t) Oxidizing properties none

### 9.2 Other safety information

Conductivity 0.01  $\mu$ S/cm at 20 °C (68 °F) Surface tension 23.2 mN/m at 20.0 °C (68.0 °F)

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

Vapors may form explosive mixture with air.

### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

### 10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

chromosulfuric acid

chromyl chloride

ethanolamine

Fluorine

Strong oxidizing agents

strong reducing agents

Nitric acid

chromium(VI) oxide

Risk of explosion with:

nonmetallic oxyhalides

halogen-halogen compounds

Chloroform

nitrating acid

nitrosyl compounds

hydrogen peroxide

halogen oxides

organic nitro compounds

peroxi compounds

Exothermic reaction with:

**Bromine** 

Alkali metals

alkali hydroxides

Halogenated hydrocarbon

Sulfur dichloride

phosphorous oxichloride

#### 10.4 Conditions to avoid

Warming.

#### 10.5 Incompatible materials

No data available

# 10.6 Hazardous decomposition products

In the event of fire: see section 5

### **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

### Acute toxicity

LD50 Oral - Rat - female - 5,800 mg/kg

Remarks: (ECHA)

Millipore - 8.22251

Millipore Sigma Symptoms: Stomach/intestinal disorders, Risk of aspiration upon vomiting., Pulmonary

failure possible after aspiration of vomit. LC50 Inhalation - Rat - 4 h - 76 mg/l - vapor

Remarks: Unconsciousness

Drowsiness Dizziness (External MSDS)

LD50 Dermal - Rabbit - 20,000 mg/kg

Remarks: (IUCLID)

### Skin corrosion/irritation

Skin - Rabbit

Result: Mild skin irritation - 24 h

(Draize Test) Remarks: (RTECS)

### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation - 24 h

(Draize Test) Remarks: (RTECS)

### Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative Remarks: (ECHA)

Chronic exposure may cause dermatitis.

### Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Metabolic activation: without metabolic activation

Method: OECD Test Guideline 476

Result: negative **Carcinogenicity** 

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Millipore - 8.22251

*Aillipore* 

Page 9 of 13

### Reproductive toxicity

No data available

### Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Narcotic effects

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

### Specific target organ toxicity - repeated exposure

No data available

# **Aspiration hazard**

No data available

#### 11.2 Additional Information

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption:

Headache

Salivation

Nausea

Vomiting

Dizziness

narcosis

Coma

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Kidney - Irregularities - Based on Human Evidence

Skin - Dermatitis - Based on Human Evidence

# **SECTION 12: Ecological information**

### 12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) -

6,210 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia

and other aquatic

invertebrates

static test LC50 - Daphnia pulex (Water flea) - 8,800 mg/l - 48 h

Remarks: (ECHA)

Toxicity to algae static test NOEC - M.aeruginosa - 530 mg/l - 8 d

(DIN 38412)

Remarks: (maximum permissible toxic concentration)

(IUCLID)

Millipore - 8.22251

IilliPORE

Page 10 of 13

Toxicity to bacteria static test EC50 - activated sludge - 61.15 mg/l - 30 min

(OECD Test Guideline 209)

Toxicity to daphnia flow-through test NOEC - Daphnia magna (Water flea) - 2,212 mg/l

and other aquatic - 28 d

invertebrates(Chronic Remarks: (ECHA)

toxicity)

# 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 91 % - Readily biodegradable.

(OECD Test Guideline 301B)

Biochemical Oxygen 1,850 mg/g

Demand (BOD) Remarks: (IUCLID)

Chemical Oxygen 2,070 mg/g

Demand (COD) Remarks: (IUCLID)

Theoretical oxygen 2,200 mg/g demand Remarks: (Lit.)

### 12.3 Bioaccumulative potential

Does not bioaccumulate.

# 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

# 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

#### **Product**

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

### **SECTION 14: Transport information**

DOT (US)

UN number: 1090 Class: 3 Packing group: II

Millipore - 8.22251

Page 11 of 13



Proper shipping name: Acetone Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No

**IMDG** 

UN number: 1090 Class: 3 Packing group: II EMS-No: F-

E, S-D

Proper shipping name: ACETONE

**IATA** 

UN number: 1090 Class: 3 Packing group: II

Proper shipping name: Acetone

# **SECTION 15: Regulatory information**

# **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	5000

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

# **SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by

SARA Title III, Section 313.

**US State Regulations** 

**Massachusetts Right To Know** 

acetone 67-64-1

Pennsylvania Right To Know

acetone 67-64-1

**Maine Chemicals of High Concern** 

Product does not contain any listed chemicals

**Vermont Chemicals of High Concern** 

Product does not contain any listed chemicals

**Washington Chemicals of High Concern** 

Product does not contain any listed chemicals

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

Millipore - 8.22251

Page 12 of 13



#### TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### **SECTION 16: Other information**

#### **Further information**

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.13 Revision Date: 09/08/2024 Print Date: 09/09/2024

Millipore - 8.22251

