

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking			
1.1	Product identifiers		
	Product name	:	MCE 0.025UM WH PL 25MM 100/PK
	Product Number Catalogue No. Brand		VSWP02500 638164 Millipore
1.2	.2 Relevant identified uses of the substance or mixture and uses advised against		
	Identified uses Uses advised against	-	Filtration The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.
1.3	3 Details of the supplier of the safety data sheet		
	Company	:	Sigma-Aldrich Inc. 3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES
	Telephone Fax	:	+1 314 771-5765 +1 800 325-5052
1.4	.4 Emergency telephone		
	Emergency Phone #	:	800-424-9300 CHEMTREC (USA) +1-703- 527-3887 CHEMTREC (International) 24

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable solids (Category 1), H228 Short-term (acute) aquatic hazard (Category 2), H401 Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

Hours/day; 7 Days/week

2.2 GHS Label elements, including precautionary statements

Millipore - VSWP02500

Page 1 of 12



Pictogram	
Signal Word	Danger
Hazard Statements H228 H401 H412	Flammable solid. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.
Precautionary Statements P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P240 P241 P273 P280 P370 + P378	Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Avoid release to the environment. Wear protective gloves/ eye protection/ face protection. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component		Classification	Concentration
Octylphenol polye	ethoxyethanol		
CAS-No.	9036-19-5	Acute Tox. 4; Skin Irrit. 2; Eye Dam. 1; Aquatic Acute 1; Aquatic Chronic 1; H302, H315, H318, H400, H410 M-Factor - Aquatic Acute: 10 - Aquatic Chronic: 1	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Millipore - VSWP02500

Page 2 of 12



In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides Combustible. Spontaneous ignition at elevated temperatures. Development of hazardous combustion gases or vapours possible in the event of fire. Fire may cause evolution of: nitrogen oxides, nitrous gases

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Protective equipment see section 8.

For personal protection see section 8.

6.2 Environmental precautions Do not let product enter drains.

Millipore - VSWP02500

Page 3 of 12



6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Observe label precautions.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry. Keep away from heat and sources of ignition. Keep away from direct sunlight.Performing regular visual inspections of membranes and keeping accurate records of recommended shelf life can reduce the risk of membrane deterioration. Shelf-life limited when kept above +25°C. Recommended storage humidity: 30 - 70 %. Verify on a regular basis housekeeping, temperature and humidity. Designated "Flammable Material" storage areas must be engineered according to local regulations. Rotate stock. Improper storage conditions can accelerate deterioration of the membrane in advance of expiration date. Perform regular visual inspections of stored materials to ensure early stages of deterioration does not advance. Early stages of deterioration: Amber or yellow discoloration. Advanced stages of deterioration, safely dispose of product according to local regulations. Storage under improper conditions could lead to the membrane self-decomposing at ambient temperatures with the formation of nitrous vapors or self ignition. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 4.1B: Flammable solid hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

Millipore - VSWP02500

Page 4 of 12



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact

Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:KCL 741 Dermatril® L

Respiratory protection

Recommended Filter type: Filter P 1 (acc. to DIN 3181) for solid particles of inert substances

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented. required when dusts are generated.

Control of environmental exposure

Do not let product enter drains.

Millipore - VSWP02500

Page 5 of 12



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: solid Color: colored
b)	Odor	No data available
c)	Odor Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	No data available
f)	Initial boiling point and boiling range	No data available
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	The substance or mixture is a flammable solid with the category 1.
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapor pressure	No data available
I)	Vapor density	No data available
m)	Density	No data available
	Relative density	No data available
n)	Water solubility	No data available
0)	Partition coefficient: n-octanol/water	No data available
p)	Autoignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	Not classified as explosive.
t)	Oxidizing properties	none
Oth	er safety informatio	n

9.2 Other safety information No data available

Millipore - VSWP02500

Page 6 of 12



SECTION 10: Stability and reactivity

10.1 Reactivity

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

10.2 Chemical stability

Product is sensitive to light and moisture. Prolonged exposure to air may cause discolouration.

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with: Oxidizing agents Bases Strong acids

10.4 Conditions to avoid

Heating (decomposition). Exposure to sunlight.

- **10.5 Incompatible materials** No data available
- **10.6 Hazardous decomposition products** In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity Oral: No data available

Inhalation: No data available

Dermal: No data available

Skin corrosion/irritation Remarks: No data available

Serious eye damage/eye irritation Remarks: No data available

Respiratory or skin sensitization No data available

Germ cell mutagenicity No data available

Carcinogenicity Carcinogenicity - No data available

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

Millipore - VSWP02500

Page 7 of 12



identified as probable, possible or confirmed human carcinogen by IARC.

- NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Reproductive toxicity - No data availableDevelopmental Toxicity - No data available**Specific target organ toxicity - single exposure** No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

11.2 Additional Information

Risk of methaemoglobin formation. After uptake:

Risk of methaemoglobin formation.

However, when the product is handled appropriately, hazardous effects are unlikely to occur.

Handle in accordance with good industrial hygiene and safety practice.

Components

Octylphenol polyethoxyethanol

Acute toxicity

LD50 Oral - Rat - 1,900 - 5,000 mg/kg Remarks: (External MSDS) Symptoms: Vomiting, Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract., Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and pneumonitis. Inhalation: No data available LD50 Dermal - Rabbit - > 3,000 mg/kg Remarks: (External MSDS)

Skin corrosion/irritation

Skin - Rabbit Result: irritating - 4 h (OECD Test Guideline 404) Remarks: The value is given in analogy to the following substances: 4-(1,1,3,3tetramethylbutyl)phenol

Serious eye damage/eye irritation

Eyes - Rabbit Result: Risk of serious damage to eyes. Millipore - VSWP02500

Page 8 of 12



(Draize Test) Remarks: Risk of corneal clouding.

Respiratory or skin sensitization

Sensitisation test: - Human Result: negative Remarks: (External MSDS) Patch test on human volunteers did not demonstrate sensitization properties.

Germ cell mutagenicity No data available

Carcinogenicity

No data available

Reproductive toxicity

Ingestion of excessive amounts by pregnant animals resulted in maternal and fetal toxicity. Did not show teratogenic effects in animal experiments.

Specific target organ toxicity - single exposure

Acute oral toxicity - Vomiting, Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract., Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and pneumonitis.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture No data available	
Toxicity to daphnia and other aquatic invertebrates	Remarks: No data available
Toxicity to algae	Remarks: No data available
Toxicity to bacteria	Remarks: No data available
Toxicity to fish(Chronic toxicity)	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	Remarks: No data available

12.2 Persistence and degradability No data available

Millipore - VSWP02500

Page 9 of 12



12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties No data available

12.7 Other adverse effects

Discharge into the environment must be avoided.

Components

Octylphenol polyethoxyethanol

Toxicity to fish	semi-static test LC50 - Leuciscus idus (Golden orfe) - 0.26 mg/l - 96 h (OECD Test Guideline 203) Remarks: The value is given in analogy to the following substances: 4-(1,1,3,3-tetramethylbutyl)phenol
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 0.011 mg/l - 48 h Remarks: (ECOTOX Database) The value is given in analogy to the following substances: 4- (1,1,3,3-tetramethylbutyl)phenol
Toxicity to algae	static test EC50 - Pseudokirchneriella subcapitata (green algae) - 1.9 mg/l - 96 h Remarks: (ECHA) The value is given in analogy to the following substances: 4- (1,1,3,3-tetramethylbutyl)phenol
Toxicity to fish(Chronic toxicity)	flow-through test - Danio rerio (zebra fish) - 0.012 mg/l (OECD Test Guideline 210) Remarks: The value is given in analogy to the following substances: 4-(1,1,3,3-tetramethylbutyl)phenol
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	semi-static test NOEC - Daphnia magna (Water flea) - 0.03 mg/l - 21 d (OECD Test Guideline 202) Remarks: The value is given in analogy to the following substances: 4-(1,1,3,3-tetramethylbutyl)phenol

Millipore - VSWP02500

Page 10 of 12



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 3270 Class: 4.1 Packing group: II Proper shipping name: Nitrocellulose membrane filters Reportable Quantity (RQ): 100 lbs Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 3270 Class: 4.1 Packing group: II EMS-No: F-A, S-I Proper shipping name: NITROCELLULOSE MEMBRANE FILTERS

ΙΑΤΑ

UN number: 3270 Class: 4.1 Packing group: II Proper shipping name: Nitrocellulose membrane filters

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Reportable Quantity F0	03	lbs
------------------------	----	-----

Massachusetts Right To Know Components

:

cellulose nitrate	9004-70-0	1989-08-11
Pennsylvania Right To Know Components cellulose nitrate	CAS-No. 9004-70-0	Revision Date 1989-08-11

CAS No

Millipore - VSWP02500

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada



Page 11 of 12

Revuision Date

California Prop. 65 Components

, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.ethanol CAS-No. 64-17-5 **Revision Date**

SECTION 16: Other information

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com. Version: 8.9 Revision Date: 03/02/2024 Print Date: 07/14/2024

Millipore - VSWP02500

Page 12 of 12

