

## SAFETY DATA SHEET

Version 6.5  
Revision Date 03/02/2024  
Print Date 07/14/2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Isopropyl alcohol

Product Number : W292907

Brand : Aldrich

Index-No. : 603-117-00-0

CAS-No. : 67-63-0

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

**1.3 Details of the supplier of the safety data sheet**

Company : Sigma-Aldrich Inc.  
3050 SPRUCE ST  
ST. LOUIS MO 63103  
UNITED STATES

Telephone : +1 314 771-5765

Fax : +1 800 325-5052

**1.4 Emergency telephone**

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 2), H225

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Aldrich - W292907

Page 1 of 13

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H225

Highly flammable liquid and vapor.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

Precautionary Statements

P210

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242

Use only non-sparking tools.

P243

Take precautionary measures against static discharge.

P261

Avoid breathing mist or vapors.

P264

Wash skin thoroughly after handling.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/ eye protection/ face protection.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313

If eye irritation persists: Get medical advice/ attention.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403 + P233

Store in a well-ventilated place. Keep container tightly closed.

P403 + P235

Store in a well-ventilated place. Keep cool.

P405

Store locked up.

P501

Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

May form explosive peroxides.

---

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Synonyms

: 2-Propanol  
sec-Propyl alcohol  
Isopropyl alcohol  
Isopropanol

Formula : C<sub>3</sub>H<sub>8</sub>O  
 Molecular weight : 60.10 g/mol  
 CAS-No. : 67-63-0  
 EC-No. : 200-661-7  
 Index-No. : 603-117-00-0

Component	Classification	Concentration
<b>2-Propanol</b>		
	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336 Concentration limits: >= 20 %: STOT SE 3, H336;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Call in physician.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>) Foam Dry powder

Aldrich - W292907

Page 3 of 13

**Unsuitable extinguishing media**

For this substance/mixture no limitations of extinguishing agents are given.

**5.2 Special hazards arising from the substance or mixture**

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

**5.3 Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus.

**5.4 Further information**

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

**6.2 Environmental precautions**

Do not let product enter drains. Risk of explosion.

**6.3 Methods and materials for containment and cleaning up**

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb® ).

Dispose of properly. Clean up affected area.

**6.4 Reference to other sections**

For disposal see section 13.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling****Advice on safe handling**

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

**Advice on protection against fire and explosion**

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

**Hygiene measures**

Change contaminated clothing. Wash hands after working with substance.

For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

### Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Handle and store under inert gas. hygroscopic

### Storage class

Storage class (TRGS 510): 3: Flammable liquids

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
2-Propanol	67-63-0	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Not classifiable as a human carcinogen		
		STEL	400 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Not classifiable as a human carcinogen		
		ST	500 ppm 1,225 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits
		TWA	400 ppm 980 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits
		TWA	400 ppm 980 mg/m <sup>3</sup>	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	400 ppm 980 mg/m <sup>3</sup>	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	500 ppm 1,225 mg/m <sup>3</sup>	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

#### Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
2-Propanol	67-63-0	Acetone	40 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at end of workweek			

**Derived No Effect Level (DNEL)**

Application Area	Routes of exposure	Health effect	Value
Workers	Inhalation	Long-term systemic effects	500 mg/m <sup>3</sup>
Workers	Skin contact	Long-term systemic effects	888mg/kg BW/d
Consumers	Inhalation	Long-term systemic effects	89 mg/m <sup>3</sup>
Consumers	Skin contact	Long-term systemic effects	319mg/kg BW/d
Consumers	Ingestion	Long-term systemic effects	26mg/kg BW/d

**Predicted No Effect Concentration (PNEC)**

Compartment	Value
Soil	28 mg/kg
Sea water	140.9 mg/l
Fresh water	140.9 mg/l
Sea sediment	552 mg/kg
Fresh water sediment	552 mg/kg

**8.2 Exposure controls****Appropriate engineering controls**

Change contaminated clothing. Wash hands after working with substance.

**Personal protective equipment****Eye/face protection**

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

**Skin protection**

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Chloroprene

Minimum layer thickness: 0.65 mm

Break through time: 120 min

Material tested: KCL 720 Camapren®

**Body Protection**

Flame retardant antistatic protective clothing.

### Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

### Control of environmental exposure

Do not let product enter drains. Risk of explosion.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

a) Appearance	Form: liquid Color: colorless
b) Odor	alcohol-like
c) Odor Threshold	1 ppm
d) pH	at 20 °C (68 °F) neutral
e) Melting point/freezing point	Melting point/range: -89.5 °C (-129.1 °F) - lit.
f) Initial boiling point and boiling range	82 °C 180 °F - lit.
g) Flash point	12.0 °C (53.6 °F) - closed cup
h) Evaporation rate	3.0
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 13.4 %(V) Lower explosion limit: 2 %(V)
k) Vapor pressure	43 hPa at 20 °C (68 °F)
l) Vapor density	2.07
m) Density	0.785 g/cm <sup>3</sup> at 25 °C (77 °F) - lit.
Relative density	No data available
n) Water solubility	soluble
o) Partition coefficient: n-octanol/water	log Pow: 0.05 - Bioaccumulation is not expected.
p) Autoignition temperature	425.0 °C (797.0 °F)
q) Decomposition	Distillable in an undecomposed state at normal pressure.

Aldrich - W292907

Page 7 of 13

temperature

- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties none

## 9.2 Other safety information

Minimum ignition energy	0.65 mJ
Conductivity	< 0.1 $\mu$ S/cm
Surface tension	20.8 mN/m at 25.0 °C (77.0 °F)
Relative vapor density	2.07

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Vapors may form explosive mixture with air.

### 10.2 Chemical stability

Reacts with air to form peroxides.

The product is chemically stable under standard ambient conditions (room temperature) .

Test for peroxide formation before distillation or evaporation. Test for peroxide formation or discard after 1 year.

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air.

### 10.4 Conditions to avoid

Warming.

### 10.5 Incompatible materials

rubber, various plastics, oils

### 10.6 Hazardous decomposition products

In the event of fire: see section 5

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 5,840 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 37.5 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - 12,800 mg/kg

Remarks: (RTECS)

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h

(OECD Test Guideline 404)

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation

(OECD Test Guideline 405)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

#### Respiratory or skin sensitization

Buehler Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

#### Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: In vivo micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

#### Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available

#### **Specific target organ toxicity - single exposure**

Inhalation, Oral - May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

#### **Specific target organ toxicity - repeated exposure**

No data available

#### **Aspiration hazard**

No data available

### **11.2 Additional Information**

RTECS: NT8050000

Central nervous system depression, prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects., Aspiration may lead to:, Lung edema, Pneumonia

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption:

Headache  
Dizziness  
inebriation  
Unconsciousness  
narcosis

After uptake of large quantities:

Coma

Handle in accordance with good industrial hygiene and safety practice.

Kidney - Irregularities - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 9,640 mg/l - 96 h (OECD Test Guideline 203)
------------------	---

Aldrich - W292907

Page 10 of 13

Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 13,299 mg/l - 48 h Remarks: (IUCLID)
Toxicity to algae	IC50 - Desmodesmus subspicatus (green algae) - > 1,000 mg/l - 72 h Remarks: (IUCLID)
Toxicity to bacteria	EC5 - Pseudomonas putida - 1,050 mg/l - 16 h Remarks: (Lit.)

## 12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 5 d Result: 53 % - Readily biodegradable. (Directive 67/548/EEC, Annex V, C.6)
Theoretical oxygen demand	2,400 mg/g Remarks: (Lit.)
Ratio BOD/ThBOD	49 % Remarks: (IUCLID)

## 12.3 Bioaccumulative potential

No bioaccumulation is to be expected (log Pow ≤ 4).

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

## 12.6 Endocrine disrupting properties

No data available

## 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See [www.retrologistik.com](http://www.retrologistik.com) for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

---

## SECTION 14: Transport information

### DOT (US)

UN number: 1219 Class: 3 Packing group: II  
Proper shipping name: Isopropanol  
Reportable Quantity (RQ):  
Poison Inhalation Hazard: No

### IMDG

UN number: 1219 Class: 3 Packing group: II EMS-No: F-E, S-D  
Proper shipping name: ISOPROPANOL

### IATA

UN number: 1219 Class: 3 Packing group: II  
Proper shipping name: Isopropanol

---

## SECTION 15: Regulatory information

### SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

2-Propanol	CAS-No. 67-63-0	Revision Date 2007-03-01
------------	--------------------	-----------------------------

### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

### Massachusetts Right To Know Components

2-Propanol	CAS-No. 67-63-0	Revision Date 2007-03-01
------------	--------------------	-----------------------------

### Pennsylvania Right To Know Components

2-Propanol	CAS-No. 67-63-0	Revision Date 2007-03-01
------------	--------------------	-----------------------------

---

## SECTION 16: Other information

### Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact

with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

Version: 6.5

Revision Date: 03/02/2024

Print Date: 07/14/2024