

# SAFETY DATA SHEET

Version 6.9 Revision Date 09/06/2024 Print Date 09/07/2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifiers

Product name : Diethyl ether

Product Number : 346136 Brand : SIGALD

Index-No. : 603-022-00-4 CAS-No. : 60-29-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 1), H224 Acute toxicity, Oral (Category 4), H302

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

SIGALD - 346136

Page 1 of 14



Short-term (acute) aquatic hazard (Category 3), H402 Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal	Word	Danger
--------	------	--------

Hazard Statements

H224 Extremely flammable liquid and vapor.

H302 Harmful if swallowed.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary Statements** 

P210	Keep away	from heat/	′ sparks/	open flames	/ hot surfaces. No

smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel

unwell. Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal

plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

May form explosive peroxides.

Repeated exposure may cause skin dryness or cracking.

May form explosive peroxides.

SIGALD - 346136

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Synonyms : Ether

Ethyl ether

Formula :  $C_4H_{10}O$ 

Molecular weight : 74.12 g/mol CAS-No. : 60-29-7 EC-No. : 200-467-2 Index-No. : 603-022-00-4

Component	Classification	Concentration
Diethyl ether		
	Flam. Liq. 1; Acute Tox. 4; STOT SE 3; H224, H302, H336 Concentration limits: >= 20 %: STOT SE 3, H336;	<= 100 %

butyl hydroxytoluene (BHT)				
	Aquatic Acute 1; Aquatic Chronic 1; H400, H410 M-Factor - Aquatic Acute: 1 - Aquatic Chronic: 1	>= 1 - < 5 %		

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first-aid measures

#### **General advice**

Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Call in physician.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

## In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

#### If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

SIGALD - 346136

Page 3 of 14



## 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment needed

No data available

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

# Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

# Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

#### 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

#### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

#### 5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

#### 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

#### 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb® ). Dispose of properly. Clean up affected area.

## 6.4 Reference to other sections

For disposal see section 13.

SIGALD - 346136



#### **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

## Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

## Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

## **Hygiene measures**

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Light sensitive. Heat sensitive. Air sensitive. Test for peroxide formation periodically and before distillation.

#### Storage class

Storage class (TRGS 510): 3: Flammable liquids

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Ingredients with workplace control parameters



Component	CAS-No.	Value	Control parameters	Basis	
Diethyl ether	60-29-7	TWA	400 ppm	USA. ACGIH Threshold Limit Values (TLV)	
		STEL	500 ppm	USA. ACGIH Threshold Limit Values (TLV)	
		TWA	400 ppm 1,200 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
		STEL	500 ppm 1,500 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
		PEL	400 ppm 1,200 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
butyl hydroxytoluene (BHT)	128-37-0	TWA	2 mg/m3	USA. ACGIH Threshold Limit Values (TLV)	
	Remarks	Not classifiable as a human carcinogen			
		TWA	10 mg/m3	USA. NIOSH Recommended Exposure Limits	
		PEL	10 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	

## 8.2 Exposure controls

#### **Appropriate engineering controls**

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

## Personal protective equipment

#### **Eye/face protection**

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

## Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact Material: Viton®

Minimum layer thickness: 0.7 mm Break through time: 30 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

SIGALD - 346136 Page 6 of 14



## **Body Protection**

Flame retardant antistatic protective clothing.

#### **Respiratory protection**

Recommended Filter type: Filter type AX

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented. required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

#### Control of environmental exposure

Do not let product enter drains. Risk of explosion.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor sweet, ether-likec) Odor Threshold No data availabled) pH No data available

e) Melting point/ range: -116 °C (-177 °F) - lit.

point/freezing point

f) Initial boiling point 34.6 °C 94.3 °F - lit.

and boiling range

g) Flash point -40 °C (-40 °F)

h) Evaporation rate No data availablei) Flammability (solid, No data available

gas)

j) Upper/lower Upper explosion limit: 36 %(V) flammability or Lower explosion limit: 1.7 %(V)

explosive limits

k) Vapor pressure 189 hPa at 0 °C (32 °F)

389 hPa at 10 °C(50 °F) 563 hPa at 20 °C(68 °F) 863 hPa at 30 °C(86 °F) 1,228 hPa at 40 °C(104 °F) 2,311 hPa at 60 °C(140 °F)

I) Vapor density 2.56 - (Air = 1.0)

m) Density 0.706 g/mL at 25 °C (77 °F) - lit.

Relative density No data available

SIGALD - 346136

Millipore SigMa n) Water solubility 65 g/l at 20 °C (68 °F) - completely soluble

o) Partition coefficient: log Pow: 1.1 - Bioaccumulation is not expected.

n-octanol/water

p) Autoignition 175 °C (347 °F) at 1,013.25 hPa

temperature

q) Decomposition No data available

temperature

r) Viscosity No data availables) Explosive properties No data available

t) Oxidizing properties none

## 9.2 Other safety information

Relative vapor 2.56 - (Air = 1.0)

density

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Formation of peroxides possible.

Vapors may form explosive mixture with air.

# 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Contains the following stabilizer(s):

butyl hydroxytoluene (BHT) (<=11 %)

#### 10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

chromyl chloride

Peroxides

Risk of explosion with:

azides

halogens

halogen-halogen compounds

nonmetallic oxyhalides

Strong oxidizing agents

chromium(VI) oxide

halogen oxides

peroxi compounds

perchloric acid

perchlorates

Nitric acid

nitrating acid

Oxygen

Ozone

turpentine oils and/or turpentine substitutes

nitrates

SIGALD - 346136

Millipore SigMa metallic chlorides
salts of oxyhalogenic acids
nitrogen oxides
nonmetallic oxides
chromosulfuric acid
chlorates
hydrogen peroxide
permanganic acid
sulfuric acid
with
Nitric acid
sulfur
Risk of explosion during distillation.
Exothermic reaction with:

## 10.4 Conditions to avoid

acid halides

Light. Heat. Air Warming. Moisture.

# 10.5 Incompatible materials

rubber, various plastics

## 10.6 Hazardous decomposition products

Peroxides

In the event of fire: see section 5

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

Acute toxicity estimate Oral - 1,224 mg/kg

(Calculation method)

LD50 Oral - Rat - 1,211 mg/kg (Diethyl ether)

Remarks: (RTECS)

Symptoms: Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and

pneumonitis.

LC50 Inhalation - Mouse - 4 h - 97.5 mg/l - vapor

(Diethyl ether) Remarks: (RTECS)

Symptoms: mucosal irritations

Acute toxicity estimate Dermal - > 5,000 mg/kg

(Calculation method)

LD50 Dermal - Rabbit - male - > 20,000 mg/kg (Diethyl ether)

(OECD Test Guideline 402)

Remarks: (ECHA)

## Skin corrosion/irritation

Skin - Rabbit (Diethyl ether) Result: No skin irritation - 4 h

SIGALD - 346136

Millipore SiGMa (OECD Test Guideline 404) Remarks: Dermatitis

#### Serious eye damage/eye irritation

Eyes - Rabbit (Diethyl ether) Result: No eye irritation (OECD Test Guideline 405)

#### Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse (Diethyl ether)

Result: negative

(OECD Test Guideline 429)

# Germ cell mutagenicity

Test Type: Mouse Test system: Embryo Remarks: DNA inhibition Test Type: Micronucleus test

(Diethyl ether)

Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

Test Type: In vitro mammalian cell gene mutation test

(Diethyl ether)

Test system: Mouse lymphoma test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative Test Type: Ames test (Diethyl ether)

Test system: Escherichia coli/Salmonella typhimurium Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative (Diethyl ether)

Test Type: Micronucleus test

Species: Mouse

Cell type: Red blood cells (erythrocytes) Application Route: Intraperitoneal Method: OECD Test Guideline 474

Result: negative

# Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

## **Reproductive toxicity**

No data available

SIGALD - 346136

**J**illiPDRE

Page 10 of 14

#### Specific target organ toxicity - single exposure

Oral - May cause drowsiness or dizziness. - Central nervous system (Diethyl ether)

## Specific target organ toxicity - repeated exposure

No data available

#### **Aspiration hazard**

No data available

#### 11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 13 Weeks - NOAEL (No observed adverse effect level) - 500 mg/kg - LOAEL (Lowest observed adverse effect level) - 2,000 mg/kg

Remarks: (ECHA) (Diethyl ether) RTECS: KI5775000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Inhalation may provoke the following symptoms: (Diethyl ether)

Cough, chest pain, Difficulty in breathing, Dizziness, Drowsiness, Contact with eyes can cause:, Redness, Provokes tears., Blurred vision, Prolonged or repeated exposure to skin causes defatting and dermatitis. (Diethyl ether)

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. (Diethyl ether)

Narcotic!

(Diethyl ether)

After absorption:

(Diethyl ether)

Salivation

ataxia (impaired locomotor coordination)

inebriation

Unconsciousness

Coma

(Diethyl ether)

Other dangerous properties can not be excluded.

(Diethyl ether)

Handle in accordance with good industrial hygiene and safety practice.

(Diethyl ether)

Liver - Ingestion may provoke the following symptoms:, Irregularities - Based on Human Evidence

Liver - Ingestion may provoke the following symptoms:, Irregularities - Based on Human Evidence (Diethyl ether)

#### **SECTION 12: Ecological information**

# 12.1 Toxicity

Toxicity to fish LC50 - Lepomis macrochirus (Bluegill sunfish) - > 10,000 mg/l - 96

h (Diethyl ether)

SIGALD - 346136 Page 11 of 14



Remarks: (IUCLID)

Toxicity to daphnia and other aquatic

EC50 - Daphnia magna (Water flea) - 1,380 mg/l - 48 h (Diethyl

ether)

invertebrates Remarks: (IUCLID)

Toxicity to algae static test ErC50 - Desmodesmus subspicatus (green algae) - > 100

> mg/l - 72 h (Diethyl ether) (OECD Test Guideline 201)

static test NOEC - Desmodesmus subspicatus (green algae) - 100

mg/l - 72 h (Diethyl ether) (OECD Test Guideline 201)

Toxicity to bacteria static test EC50 - activated sludge - 21,000 mg/l - 3 h (Diethyl

ether)

(OECD Test Guideline 209)

static test NOEC - activated sludge - 42 mg/l - 3 h (Diethyl ether)

(OECD Test Guideline 209)

Toxicity to daphnia and other aquatic invertebrates(Chronic (OECD Test Guideline 211)

semi-static test NOEC - Daphnia magna (Water flea) - > 100 mg/l -

21 d (Diethyl ether)

toxicity)

# 12.2 Persistence and degradability

Not readily biodegradable.

## 12.3 Bioaccumulative potential

No bioaccumulation is to be expected (log Pow  $\leq$  4).

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

No data available

SIGALD - 346136 Page 12 of 14

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

#### **SECTION 14: Transport information**

DOT (US)

UN number: 1155 Class: 3 Packing group: I

Proper shipping name: Diethyl ether Reportable Quantity (RQ): 101 lbs Reportable Quantity (RQ): 100 lbs Poison Inhalation Hazard: No

**IMDG** 

UN number: 1155 Class: 3 Packing group: I EMS-No: F-E, S-D

Proper shipping name: DIETHYL ETHER

**IATA** 

UN number: 1155 Class: 3 Packing group: I

Proper shipping name: Diethyl ether

## **SECTION 15: Regulatory information**

# **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Diethyl ether	60-29-7	100	101
Diethyl ether	60-29-7	100	100 (F003)

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 : Fire Hazard

**Hazards** Acute Health Hazard Chronic Health Hazard

SARA 313 : This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by

SARA Title III, Section 313.

SIGALD - 346136

Page 13 of 14

# **US State Regulations**

#### **Massachusetts Right To Know**

Diethyl ether 60-29-7 butyl hydroxytoluene (BHT) 128-37-0

## Pennsylvania Right To Know

Diethyl ether 60-29-7

## **Maine Chemicals of High Concern**

Product does not contain any listed chemicals

# **Vermont Chemicals of High Concern**

Product does not contain any listed chemicals

# **Washington Chemicals of High Concern**

Product does not contain any listed chemicals

#### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

#### **TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

# **SECTION 16: Other information**

#### **Further information**

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.9 Revision Date: 09/06/2024 Print Date: 09/07/2024

SIGALD - 346136

