

SAFETY DATA SHEET

Version 7.0 Revision Date 09/30/2024 Print Date 10/01/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Sodium ethoxide solution

Product Number : 230553

Brand : Sigma-Aldrich

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Self-heating chemicals (Category 1), H251 Skin corrosion (Category 1A), H314 Serious eye damage (Category 1), H318 Carcinogenicity, Inhalation (Category 2), H351

Sigma-Aldrich - 230553

Page 1 of 21



Specific target organ toxicity - single exposure (Category 2), Eyes, Central nervous system, H371

Short-term (acute) aquatic hazard (Category 3), H402 Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal Word	Danger
Hazard Statements H225 H251 H314 H351 H371	Highly flammable liquid and vapor. Self-heating; may catch fire. Causes severe skin burns and eye damage. Suspected of causing cancer if inhaled. May cause damage to organs (Eyes, Central nervous system). Harmful to aquatic life with long lasting effects.
Precautionary Statements	
P201 P202	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No
P233 P235 + P410 P240 P241 P242 P243 P260 P264 P270 P273 P280	Keep container tightly closed. Keep cool. Protect from sunlight. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapors. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P330 + P331 P303 + P361 + P353	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P311 P308 + P313 P363 P370 + P378	IF exposed or concerned: Call a POISON CENTER/ doctor. IF exposed or concerned: Get medical advice/ attention. Wash contaminated clothing before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant
P403 + P235	foam to extinguish. Store in a well-ventilated place. Keep cool.



P405	Store locked up.
P407	Maintain air gap between stacks/ pallets.
P420	Store away from other materials.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Reacts violently with water.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Synonyms : Sodium ethylate

Component		Classification	Concentration
ethanol			
CAS-No. EC-No. Index-No. Registration number	64-17-5 200-578-6 603-002-00-5 01-2119457610-43- XXXX	Flam. Liq. 2; Eye Irrit. 2A; H225, H319 Concentration limits: >= 50 %: Eye Irrit. 2A, H319;	>= 70 - < 90 %
sodium ethylate			
CAS-No. EC-No. Index-No.	141-52-6 205-487-5 603-041-00-8	Flam. Sol. 1; Self-heat. 1; Skin Corr. 1A; Eye Dam. 1; H228, H251, H314, H318	>= 20 - < 30 %
Methanol			
CAS-No. EC-No. Index-No. Registration number	67-56-1 200-659-6 603-001-00-X 01-2119433307-44- XXXX	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301, H331, H311, H370 Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371;	>= 3 - < 5 %
n-heptane			
CAS-No. EC-No. Index-No. Registration number	142-82-5 205-563-8 601-008-00-2 01-2119457603-38- XXXX	Flam. Liq. 2; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1; Aquatic Acute 1; Aquatic Chronic 1; H225, H315, H336, H304, H400, H410 Concentration limits: 20 %: STOT SE 3, H336; M-Factor - Aquatic Acute: 1 - Aquatic Chronic: 1	>= 0.1 - < 1 %
4-methylpentan-2-	one		
CAS-No. EC-No.	108-10-1 203-550-1	Flam. Liq. 2; Acute Tox. 4; Eye Irrit. 2A; Carc. 2;	>= 0.1 - < 1 %

Sigma-Aldrich - 230553

Millipore

Index-No.	606-004-00-4	STOT SE 3; H225, H332,	
Registration	01-2119473980-30-	H319, H351, H336	
number	XXXX	Concentration limits:	
		20 %: STOT SE 3, H335;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

Water Foam

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Sodium oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.



May not get in touch with: Water

Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols. Keep workplace dry. Do not allow product to come into contact with water.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep away from heat and sources of ignition. Never allow product to get in contact with water during storage.

Sigma-Aldrich - 230553

Page 5 of 21



Storage class

Storage class (TRGS 510): 4.2: Pyrophoric and self-heating hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Ingredients with	TTO: IXPIGG	control pur	w			
Component	CAS-No.	Value	Control parameters	Basis		
ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants		
		STEL	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)		
	Remarks	Confirmed humans	animal carcinoge	en with unknown relevance to		
		TWA	1,000 ppm 1,900 mg/m3	USA. NIOSH Recommended Exposure Limits		
		PEL	1,000 ppm 1,900 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
Methanol	67-56-1	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)		
		Danger of cutaneous absorption				
		STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)		
		Danger of cutaneous absorption				
		ST	250 ppm 325 mg/m3	USA. NIOSH Recommended Exposure Limits		
		Potential fo	r dermal absorp			
		TWA	200 ppm 260 mg/m3	USA. NIOSH Recommended Exposure Limits		
		Potential fo	r dermal absorp	tion		
		TWA	200 ppm 260 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants		
		PEL	200 ppm 260 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
		Skin				

Sigma-Aldrich - 230553 Page 6 of 21



		С	1,000 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		
		STEL	250 ppm 325 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		
n-heptane	142-82-5	TWA	85 ppm 350 mg/m3	USA. NIOSH Recommended Exposure Limits
		С	440 ppm 1,800 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	500 ppm 2,000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	400 ppm 1,600 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	500 ppm 2,000 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		TWA	400 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	500 ppm	USA. ACGIH Threshold Limit Values (TLV)
4-methylpentan- 2-one	108-10-1	STEL	75 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Confirmed animal carcinogen with unknown relevance to humans		
		TWA	50 ppm 205 mg/m3	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
		STEL	75 ppm 300 mg/m3	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
		TWA	100 ppm 410 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	20 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Confirmed humans	animal carcinog	en with unknown relevance to

Sigma-Aldrich - 230553 Page 7 of 21



TWA	50 ppm 205 mg/m3	USA. NIOSH Recommended Exposure Limits
ST	75 ppm 300 mg/m3	USA. NIOSH Recommended Exposure Limits
PEL	50 ppm 205 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
STEL	75 ppm 300 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

Biological occupational exposure limits

Biological occupational exposure inities					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Methanol	67-56-1	Methanol	15 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as	possible after exp	oosure ceases)
4-methylpentan- 2-one	108-10-1	methyl isobutyl ketone	1 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift (As soon as possible after exposure ceases)			

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm



Break through time: 30 min

Material tested: Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter type ABEK

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented. required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: viscous liquid

Color: colorless, to, dark yellowdark brown

b) Odor
c) Odor Threshold
d) pH
e) Melting
no data available
No data available
No data available

point/freezing point

 f) Initial boiling point 91 and boiling range

91 °C 196 °F at 1,013 hPa

g) Flash point 9 °C (48 °F) - closed cup

h) Evaporation rate No data availablei) Flammability (solid, No data available gas)

j) Upper/lower flammability or

No data available

explosive limits Sigma-Aldrich - 230553



k) Vapor pressure No data available
l) Vapor density No data available
m) Density 0.868 g/cm3
Relative density No data available
n) Water solubility No data available
o) Partition coefficient: n-octanol/water

p) Autoignition No data available temperature

q) Decomposition No data available temperature

r) Viscosity No data available

s) Explosive properties Not classified as explosive.

t) Oxidizing properties none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air. Self-heating; may catch fire.

10.2 Chemical stability

sensitive to moisture

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Warming. Moisture.

10.5 Incompatible materials

Water, Strong bases, Acids, Oxidizing agents, Alkali metals, Strong oxidizing agents, Ammonia, Acid chlorides, Acid anhydrides, Reducing agents, Peroxides, acids, Chlorinated solvents

10.6 Hazardous decomposition products

In the event of fire: see section 5



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available

Acute toxicity estimate Oral - 2,534 mg/kg

(Calculation method)

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of

perforation of the esophagus and the stomach.

Inhalation: No data available

Acute toxicity estimate Inhalation - 4 h - 78.48 mg/l - vapor(Calculation method)

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of

respiratory tract

Dermal: No data available

Acute toxicity estimate Dermal - > 5,000 mg/kg

(Calculation method)

Skin corrosion/irritation

Remarks: Mixture causes severe burns.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye damage.

Risk of blindness!

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Evidence of a carcinogenic effect if inhaled.

IARC: 2B - Group 2B: Possibly carcinogenic to humans (4-methylpentan-2-one)

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Mixture may cause damage to organs. - Eyes, Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Sigma-Aldrich - 230553

Millipore SigMa

11.2 Additional Information

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Stomach - Irregularities - Based on Human Evidence

Liver - Irregularities - Based on Human Evidence

Components

ethanol

Acute toxicity

LD50 Oral - Rat - male and female - 10,470 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 124.7 mg/l - vapor

(OECD Test Guideline 403) Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 24 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.

(OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Remarks: (in analogy to similar products)

The value is given in analogy to the following substances: Methanol

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Result: negative

Method: OECD Test Guideline 478

Species: Mouse - male

Result: Positive results were obtained in some in vivo tests.

Carcinogenicity

No data available



Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Aspiration hazard

No data available

sodium ethylate

Acute toxicity

LD50 Oral - Rat - male and female - 598 mg/kg

(OECD Test Guideline 401) Inhalation: No data available Dermal: No data available

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Causes severe burns. - 3 min

(OECD Test Guideline 404)

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Methanol

Acute toxicity

Acute toxicity estimate Oral - 100.1 mg/kg (Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Sigma-Aldrich - 230553

AilliPORE

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation Remarks: (ECHA)

Remarks: Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation Remarks: (ECHA)

Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Bone marrow

Result: negative

Carcinogenicity Did not show carcino

Did not show carcinogenic effects in animal experiments.

Reproductive toxicity

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Acute oral toxicity - Nausea, Vomiting

Acute inhalation toxicity - Irritation symptoms in the respiratory tract.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

n-heptane

Acute toxicity

LD50 Oral - Rat - male and female - > 5,000 mg/kg

(OECD Test Guideline 401)

Remarks: The value is given in analogy to the following substances: isooctane

LC50 Inhalation - Rat - male and female - 4 h - > 29.29 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male and female - > 2,000 mg/kg

(OECD Test Guideline 402)

Remarks: The value is given in analogy to the following substances: isooctane

Skin corrosion/irritation

Skin - Rabbit

Result: Irritating to skin. - 24 h (OECD Test Guideline 404)

Remarks: The value is given in analogy to the following substances: isooctane Remarks: Repeated or prolonged exposure may cause skin irritation and dermatitis,

due to degreasing properties of the product.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation (OECD Test Guideline 405)

Remarks: The value is given in analogy to the following substances: isooctane

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Remarks: Germ cell mutagenicity

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Result: negative

Test Type: Chromosome aberration test in vitro

Test system: rat hepatocytes

Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

No data available

Sigma-Aldrich - 230553

4illiPORe

Page 15 of 21

Aspiration hazard

May be fatal if swallowed and enters airways. Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

4-methylpentan-2-one

Acute toxicity

LD50 Oral - Rat - 2,080 mg/kg (OECD Test Guideline 401)

LC50 Inhalation - Rat - male - 4 h - 11.6 mg/l - vapor

(OECD Test Guideline 403) Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: slight irritation - 72 h (OECD Test Guideline 405)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: rat hepatocytes

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Bone marrow

Result: negative

Carcinogenicity

Suspected of causing cancer if inhaled.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Respiratory Tract

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

Components

ethanol

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead

minnow) - 15,300 mg/l - 96 h

(US-EPA)

Toxicity to daphnia

and other aquatic

- 48 h

invertebrates

Remarks: (ECHA)

Toxicity to algae static test ErC50 - Chlorella vulgaris (Fresh water algae) - 275

static test LC50 - Ceriodaphnia dubia (water flea) - 5,012 mg/l

mg/l - 72 h

(OECD Test Guideline 201)

Toxicity to bacteria static test IC50 - activated sludge - > 1,000 mg/l - 3 h

(OECD Test Guideline 209)

Toxicity to semi-static test NOEC - Danio rerio (zebra fish) - 250 mg/l -

fish(Chronic toxicity) 120 h

Remarks: (ECHA)

Toxicity to daphnia semi-static test NOEC - Daphnia magna (Water flea) - 9.6 mg/l

and other aquatic - 9 d

y to applific Od

Sigma-Aldrich - 230553

Page 17 of 21



invertebrates(Chronic Remarks: (ECHA)

toxicity)

sodium ethylate

No data available

Methanol

Toxicity to fish flow-through test LC50 - Lepomis macrochirus (Bluegill) -

15,400.0 mg/l - 96 h

(US-EPA)

Toxicity to daphnia

and other aquatic

invertebrates

semi-static test EC50 - Daphnia magna (Water flea) - 18,260

mg/l - 96 h

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green

algae) - ca. 22,000.0 mg/l - 96 h

(OECD Test Guideline 201)

static test IC50 - activated sludge - > 1,000 mg/l - 3 h Toxicity to bacteria

(OECD Test Guideline 209)

Toxicity to

fish(Chronic toxicity)

NOEC - Oryzias latipes (Orange-red killifish) - 7,900 mg/l - 200

Remarks: (External MSDS)

n-heptane

Toxicity to fish LL50 - Rainbow darter (Etheostoma caeruleum) - > 13.4 mg/l

(OECD Test Guideline 203)

Remarks: (ECHA)

Toxicity to daphnia

and other aquatic invertebrates

static test EC50 - Daphnia magna (Water flea) - 0.23 mg/l - 21

Remarks: (ECHA)

(in analogy to similar products)

Toxicity to algae EL50 - Pseudokirchneriella subcapitata (green algae) - 29 mg/l

- 72 h

(OECD Test Guideline 201)

Remarks: (ECHA)

NOELR - Pseudokirchneriella subcapitata (green algae) - 6.3

mg/l - 72 h

(OECD Test Guideline 201)

Remarks: (ECHA)

4-methylpentan-2-one

Toxicity to fish static test LC50 - Danio rerio (zebra fish) - > 179 mg/l - 96 h

Sigma-Aldrich - 230553

Page 18 of 21

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic

static test EC50 - Daphnia magna (Water flea) - > 200 mg/l -

48 h

invertebrates (OECD Test Guideline 202)

Toxicity to daphnia and other aquatic invertebrates(Chronic semi-static test NOEC - Daphnia - 30 - 78 mg/l - 21 d

(OECD Test Guideline 211)

toxicity)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14: Transport information

DOT (US)

UN number: 3274 Class: 3 (8) Packing group: II

Proper shipping name: Alcoholates solution, n.o.s. (sodium ethylate, ethanol)

Reportable Quantity (RQ):

Poison Inhalation Hazard: No.

IMDG

UN number: 3274 Class: 3 (8) Packing group: II EMS-No: F-E, S-C Proper shipping name: ALCOHOLATES SOLUTION, N.O.S. (sodium ethylate, ethanol)

IATA

UN number: 3274 Class: 3 (8) Packing group: II

Proper shipping name: Alcoholates solution, n.o.s. (sodium ethylate, ethanol)

SECTION 15: Regulatory information

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

Sigma-Aldrich - 230553

Page 19 of 21



SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312

: Fire Hazard

Hazards

Acute Health Hazard Chronic Health Hazard

SARA 313 : The following components are subject to reporting

levels established by SARA Title III, Section 313:

Methanol 67-56-1 >= 1 - < 5 %

4- 108-10-1 >= 0.1 - < 1 %

methylpentan-

2-one

US State Regulations

Massachusetts Right To Know

ethanol	64-17-5
Methanol	67-56-1

Pennsylvania Right To Know

ethanol	64-17-5
Methanol	67-56-1
ethyl acetate	141-78-6
4-methylpentan-2-one	108-10-1

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California Prop. 65

WARNING: This product can expose you to chemicals including ethanol, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16: Other information

Relevant changes since previous version

5. Fire-fighting measures

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 7.0 Revision Date: 09/30/2024 Print Date: 10/01/2024

